



		KEYED NOTES					
MARK	QTY	DESCRIPTION					
1	1	PRECAST CONCRETE LINT INTERCEPTOR					
2	2	GALVANIZED RISER SUPPORT					
3	1	4" or 6" PVC MANIFOLD					
4	1	TAPERED WALL					
5	1	MONOLITHIC BAFFLE					
6	2	INLET AND OUTLET SCH 40 PVC PIPING					
7	2	RESILIENT RUBBER BOOT					
8	2	24" CAST IRON FRAME & COVER					
9	2	CONCRETE EXTENSION RINGS AS REQ'D					
10	1	4" VENT COUPLING					
11	1	JOINT SEALED w/ PLASTIC FLEXIBLE GASKET (RAMNEK)					
12	1	NAMEPLATE INDICATING: MFG: Parkusa 888-611-Park MODEL: LT-01 DATE MANUFACTURED					
13	-	INTERIOR LINING EPOXY (OPTIONAL)					





**NAMEPLATE** 



LINT INTERCEPTOR SCHEDULE										
MODEL NO.	CAPACITY USGal	GREASE CAP. (LBS)			WIDTH W	HEIGHT H	INLET FL1	OUTLET FL2		
LT-500	500	1,200	9,500	7'-10"	4'-4"	4'-6"	3'-3"	3'-0"		
LT-750	750	1,700	9,900	7'-10"	4'-4"	6'-0"	4'-5"	4'-2"		

OTHER SIZES ARE AVAILABLE. CONTACT US FOR MORE INFORMATION

## **SPECIFICATIONS**

CONCRETE:

CLASS I/II CONCRETE WITH DESIGN STRENGTH OF 4500 PSI AT 28 DAYS. UNIT IS OF MONOLITHIC CONSTRUCTION AT FLOOR, FIRST STAGE OF WALL AND BAFFLE WITH SECTIONAL RISER TO REQUIRED DEPTH. (MONOLITHIC BAFFLE REQUIRED, SLIDE-IN TYPE NOT ACCEPTABLE).

REINFORCEMENT: GRADE 60 REINFORCED WITH STEEL REBAR CONFORMING TO ATSM A615 ON REQUIRED CENTERS OR EQUAL.

C.I. CASTINGS:

MANHOLE FRAMES, COVERS OR GRATES ARE MANUFACTURED OF GREY CAST IRON CONFORMING TO ASTM A48-76 CLASS 30.MANHOLE SHALL BE NOMINAL 24 INCH DIAMETER AND BE TRAFFIC DUTY.

Engineering Data

THE GREASE INTERCEPTOR IS STRUCTURALLY & HYDRAULICALLY ENGINEERED TO CONFORM TO UPC/IPC AND REGIONAL PLUMBING CODES RECOMMENDED IN MOST CITIES. CONSULT WITH LOCAL AUTHORITIES FOR SPECIFIC APPLICATION REQUIREMEMENTS.

SHOP DRAWINGS SHALL INCLUDE COMPLETE STRUCTURAL & BUOYANCY CALCULATIONS CERTIFIED BY A LICENSED PROFESSIONAL ENGINEER UPON REQUEST.

CONSULT PARKUSA FOR EXACT EXCAVATION DIMENSIONS & SHIPPING INFORMATION.



TYPICAL APPLICATIONS INCLUDE COMMERCIAL AND INDUSTRIAL LAUNDRY FACILITIES WHERE EXCESSIVE SILT & LINT MAY INTERFERE WITH THE PROPER DRAINAGE OF THE SEWER SYSTEM. THE LINT INTERCEPTOR IS GENERALLY BURIED BELOW GRADE FOR GRAVITY FLOW SEWER SYSTEMS. A SAMPLE WELL IS UTILIZED ON THE OUTLET SIDE FOR SAMPLING BY THE LOCAL WATER AUTHORITY.

@ ParkUSA. ALL RIGHTS RESERVED.







LINT INTERCEPTOR SERIES LT

	MO	DEL	500	THRU	/50	GALLON	CAPACIT	Y
PM ·	PC	DRN	ENG	DWG. NO.			,	REV.
DATE	- 2	2023				LT-01		A